

DEKALIN

a brand of
DINOL

DEKAMELT

DEKAMELT
8026

DEKAMELT 8026

ADVANCED HOT MELT PSA FOR SUPERIOR
BONDING, STABLE PROCESSING,
AND MULTI-SUBSTRATE ADHESION.

YOUR ADVANTAGES:



EXCELLENT ADHESION TO PE, PP



BALANCED TACK AND COHESION



IMPROVED THERMAL STABILITY



LOW STRINGING



SUITABLE FOR SPRAY AND SLOT DIE



PRODUCT DESCRIPTION

DEKAMELT 8026 is an advanced pressure sensitive hot melt adhesive (PSA), engineered to provide enhanced bonding performance, improved process stability, and excellent adhesion across a wide range of substrates.

PRODUCT TYPE

Pressure sensitive hot melt adhesive (PSA).

APPLICATIONS

- Bonding of flexible foams.
- Packaging applications.
- Assembly processes.
- Labeling applications.
- Industrial bonding.

APPLICATION GUIDELINES

Application temperature: 150–170 °C.

Ensure clean substrates.

Optimize pressure settings.

Extended open time.

Service Temperature up to 50 °C.

STORAGE

Shelf life: 24 months.

Store in cool, dry conditions.

SAFETY

Refer to SDS. Use PPE and proper ventilation.

DISCLAIMER

Information is based on lab tests but not binding.

Users must verify suitability.

Colour (standard)	White
Specific gravity (20°C)	0.90 - 0.94 g/cm ³
Softening point (R&B)	72 – 85°C (ASTM E28)
Viscosity (20°C)	2,500 – 3,500 mPa.s at 160°C (Brookfield, ASTM D3236)
Recommended application temperature	145 – 165°C
Packaging	Small pillows ,18 kg per carton.

All information, recommendations and safety precautions are based on in-house studies and experience and are not binding. Although the documentation has been created with great care, we do not assume any liability for errors, inaccuracies or printing errors. We reserve the right to update the product whenever we feel it is necessary. As the implementation, the condition of the substrate and the conditions under which the product is used lie outside our sphere of influence, we cannot assume any responsibility for work that has been carried out based on this documentation. We therefore recommend testing the product on site. All of our deliveries are subject to the General terms of sale and purchasing of DINOL GmbH.



Pyrmonter Straße 76, D-32676 Lügde | T. +49 5281 - 982 980 | F. +49 5281 - 982 9860 | info@dinol.com | dekalin.capsule-adhesives.com